

Connector - PV-CF-P 2,5(+)- 1795323


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Photovoltaic connector, nominal current: 15 A, nom. voltage: 1000 V, connection method: Pierce connection, color: black. Only with Huber & Suhner RADOX[®] Solar (TÜV) solar cable

RoHS

Key Commercial Data

Packing unit	50 STK
GTIN	 4 046356 651196
GTIN	4046356651196

Technical data

Dimensions

External cable diameter	5.05 mm ... 5.35 mm
-------------------------	---------------------

Ambient conditions

Degree of protection (when plugged in)	IP67
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (assembly)	-25 °C ... 50 °C

General

Design	Socket
Tightening torque nut	0.22 Nm ±0.03 Nm
Insertion force	40 N ±5 N
Disconnect force	170 N ±5 N
Pull-out force of cable >= disconnect force	> 190 N
Rated voltage	1000 V
Rated surge voltage	10 kV
Rated current (2.5 mm ²)	15 A
Nominal cross section	2.5 mm ²
Protection class	II

Connector - PV-CF-P 2,5(+)- 1795323

Technical data

Material

Color	black
Insulating material	mPPE
Contact material	Cu
Contact surface material	Ag
Flammability rating according to UL 94	V0

Connection data

Connection method	Pierce connection
Connection capacity	2.5 mm ²
Contact resistance with connected conductor	0.3 mΩ
Stripping length	10 mm
Cable type	PV1-F cables

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Dimensional drawing



Approvals

Approvals

Approvals

EAC

Ex Approvals

Connector - PV-CF-P 2,5(+) - 1795323

Approvals

Approval details

EAC		B.01742
-----	---	---------

Phoenix Contact 2018 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>