
## KEMET Part Number: T491B105M035ZT7280 Obsolete



## B45196E, Tantalum, MnO2 Tantalum, 1 uF, 20%, 35 V, SMD, Molded, 3528, Height Max = 2.1mm



General Information		
Supplier:	KEMET	
Series:	B45196E	
Dielectric:	MnO2 Tantalum	
Style:	SMD Chip	
Description:	SMD, Molded	
RoHS:	Yes	
Termination:	Tin	
Notes:	Obsolete. Old Part Number [Obsolete] Was B45196E6105M206	

Dimensions	
Footprint	3528
L	3.5mm +/-0.2mm
W	2.8mm +/-0.2mm
Н	1.9mm +/-0.2mm
S	0.7mm +/-0.3mm
F	2.2mm +/-0.1mm
K	1.4mm TYP

Specifications	
Capacitance:	1 uF
Capacitance Tolerance:	20%
Voltage DC:	35 VDC (85C), 23.45 VDC (125C)
Temperature Range:	-55/+125C
Rated Temperature:	85C
Dissipation Factor:	4%
Failure Rate:	N/A
Leakage Current:	0.5 uA

Packaging Specifications	
Packaging:	T&R, 330mm
Packaging Quantity:	8000

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

