

Audio Chassis Mount *140 Series*



Note: This product line will soon be discontinued as a stocked series. Available while quantities last. It has been replaced with **140EX Series**. For alternative solution assistance, please contact Hammond Customer Service - sales@hammfg.com or USA (716) 630-7030, Canada and International (519) 822-2960.



Features

- Insulated leads 5" (127mm) long minimum
- Stamped steel case - Diameter of 1.25" (31.8mm) and height of 1" (25.4mm) for excellent shielding - low hum pick-up.
- Frequency response 70 Hz. - 11 Khz. (+/- 1 db, ref. @ 1 Khz.)
- Case bracket - mounting hole centers are 1.9" (48.3mm)
- Net weight 2 oz.



Part No.	Typical Applications	Nominal Impedance (Ohms)		Overall Turns Ratio Pri. to Sec.	Lead Length	Case Height	Case Diameter	Mounting Holes
		Primary	Secondary					
140A	Voice Coil to Single Grid	4	60000	1:122	5.00	1.00	1.25	1.90
140B	Dyn. MIC. to Single Grid	30	60000	1:45	5.00	1.00	1.25	1.90
140C	MIC. to Single Grid	50	60000	1:34:5	5.00	1.00	1.25	1.90
140H	Bridging Line to P.P. Grids	10000	40000 ct	1:2	5.00	1.00	1.25	1.90
140K	MIC. to Single Grid	150	60000	1:2	5.00	1.00	1.25	1.90
140M	CRYS, MIC. to Base	100K	1500	8:1	5.00	1.00	1.25	1.90
140N	Dyn. MIC to Base	50	1500	1:5:5	5.00	1.00	1.25	1.90
140P	Line to Base	150/600	600/2400	1:2	5.00	1.00	1.25	1.90
140Q	Line to Line	600 ct	600 ct	1:1	5.00	1.00	1.25	1.90

Data subject to change without notice